

LLumar® iLLusions™ Decorative Window Film  
Frost Series

**Dusted Crystal (NRMV80DC PS3)**



SPECIFICATION SHEET



To view this product and the rest of the LLumar® iLLusions™ line, please visit [LLumar.com/decofilmviewer](http://LLumar.com/decofilmviewer)

**Product Description**

Create private spaces that feel open and airy with frost series decorative window films. Frosted and translucent finishes ensure privacy without sacrificing natural light. They are ideal for commercial interior glazing applications such as office partitions or to meet interior design goals at a fraction of the cost of etched glass.

**Benefits and selection criteria**

- Delicately obscures visibility for increased privacy
- Delivers light and airy definition of space
- Softly diffuses light
- Can be custom cut for a decorative or patterned appearance
- Helps shield harmful ultraviolet rays

**Specifications**

Product Name	Dusted Crystal (NRMV80DC PS3)
Product Series	Frost Series
Film Type	Vinyl
Adhesive Type	Pressure-sensitive
Usage	Interior
Widths	60", 48"
Film Thickness (excludes liner)	.003"

**Installation and Warranty**

LLumar iLLusions are professionally installed by a global network of authorized dealers in accordance with factory procedures. While installation is fast, with minimal disruption to tenants or contractors, the film is extremely durable and is backed by a limited manufacturer's warranty. Your dealer can provide you with technical information and warranty details.

**Contact Information**

Call 1-800-851-7781 or visit [solutions.llumar.com/commercial](http://solutions.llumar.com/commercial) to learn more.

**Performance Data**

	% Visible Light Transmittance	% Diffuse Visible Light Reflectance (exterior)	Privacy Film Rating
Clear Glass 1/8" (3mm) single pane	90	8	0
Dusted Crystal (NRMV80DC PS3) 1/8" (3mm) single pane	87	11	7

**Privacy Film Rating**

This number, between 0 (clear) and 10 (opaque), represents the relative difficulty an observer has in identifying the nature and character of an object located on the opposite side of the window, with the observer and the object both located at least 2 feet from the pane upon which the product has been installed.

For the most current data please go to [LLumar.com/nar-deco-specs](http://LLumar.com/nar-deco-specs)



LLumar.com

© 2014 Eastman Chemical Company. LLumar® and the LLumar® logo are trademarks of Eastman Chemical Company or one of its wholly owned subsidiaries. As used herein, © denotes registered trademark status in the U.S. only. Printed in U.S.A. (11/14)

