

LLumar® iLLusions™ Decorative Window Film
Frost Series

Dusted Crystal Poly



SPECIFICATION SHEET



To view this product and the rest of the LLumar® iLLusions™ line, please visit LLumar.com/decofilmviewer

Specifications

Product Name	Dusted Crystal Poly
Product Series	Frost Series
Film Type	Polyester
Adhesive Type	Pressure-sensitive
Usage	Interior
Width	60"
Film Thickness (excludes liner)	.003"

Performance Data

	% Visible Light Transmittance	% Diffuse Visible Light Reflectance (exterior)	Privacy Film Rating
Clear Glass 1/8" (3mm) single pane	90	8	0
Dusted Crystal Poly 1/8" (3mm) single pane	87	9	7

For the most current data please go to LLumar.com/nar-deco-specs

Product Description

Create private spaces that feel open and airy with frost series decorative window films. Frosted and translucent finishes ensure privacy without sacrificing natural light. They are ideal for commercial interior glazing applications such as office partitions or to meet interior design goals at a fraction of the cost of etched glass.

Benefits and selection criteria

- Softens light and lines for a more obscure view
- Matte finish blends well with a broad range of designs
- Softly diffuses light
- Can be custom cut for a decorative or patterned appearance
- Helps shield harmful ultraviolet rays

Installation and Warranty

LLumar iLLusions are professionally installed by a global network of authorized dealers in accordance with factory procedures. While installation is fast, with minimal disruption to tenants or contractors, the film is extremely durable and is backed by a limited manufacturer's warranty. Your dealer can provide you with technical information and warranty details.

Contact Information

Call 1-800-851-7781 or visit solutions.llumar.com/commercial to learn more.

Privacy Film Rating

This number, between 0 (clear) and 10 (opaque), represents the relative difficulty an observer has in identifying the nature and character of an object located on the opposite side of the window, with the observer and the object both located at least 2 feet from the pane upon which the product has been installed.



LLumar.com

© 2014 Eastman Chemical Company. LLumar® and the LLumar® logo are trademarks of Eastman Chemical Company or one of its wholly owned subsidiaries. As used herein, © denotes registered trademark status in the U.S. only. Printed in U.S.A. (11/14)

