LLumar® iLLusions™ Decorative Window Film

Texture Series

Frosted Glass





To view this product and the rest of the LLumar® iLLusions™ line, please visit LLumar.com/decofilmviewer

Specifications

| Product Name | Frosted Glass |
|---------------------------------|--------------------|
| Product Series | Texture Series |
| Film Type | Vinyl |
| Adhesive Type | Pressure-sensitive |
| Usage | Interior |
| Width | 48" |
| Film Thickness (excludes liner) | .004" |

| Performance Data | % Visible Light Transmittance | % Diffuse Visible Light Reflectance (exterior) | Privacy Film Rating |
|---|----------------------------------|---|------------------------|
| Clear Glass 1/8" (3mm) single pane | 90 | 8 | 0 |
| Frosted Glass 1/8" (3mm) single pane | 88 | 9 | 5 |

For the most current data please go to LLumar.com/nar-deco-specs

Product Description

LLumar textured films refract light and simulate the sparkle and clarity of a textured glass window. These translucent, flexible films are the perfect solution for hard-to-cover specialty windows. Add elegance to buildings without the cost of designer glass.

Benefits and selection criteria

- Creates a sophisticated look without the expense of etched glass
- Realistic textured finish ensures privacy and maintains brightness
- Helps shield harmful ultraviolet rays

Installation and Warranty

LLumar iLLusions are professionally installed by a global network of authorized dealers in accordance with factory procedures. While installation is fast, with minimal disruption to tenants or contractors, the film is extremely durable and is backed by a limited manufacturer's warranty. Your dealer can provide you with technical information and warranty details.

Contact Information

Call 1-800-851-7781 or visit solutions.llumar.com/commercial to learn more.

Privacy Film Rating

This number, between 0 (clear) and 10 (opaque), represents the relative difficulty an observer has in identifying the nature and character of an object located on the opposite side of the window, with the observer and the object both located at least 2 feet from the pane upon which the product has been installed.









