

LLumar® iLLusions™ Decorative Window Film
Color Frost Series
Graphite



SPECIFICATION SHEET



To view this product and the rest of the LLumar® iLLusions™ line, please visit LLumar.com/decofilmviewer

Product Description

Our Color Frost Series enlivens the timeless look of matte frosts with enriching color. This thoughtfully curated selection offers translucent and sandblasted effects in a range of neutrals that includes both warm and cool tones.

Each style creates ambience and privacy at a fraction of the cost of custom glass. Browse and imagine clear glass partitions, stairways, and even furniture as eye-catching design elements.

Benefits and selection criteria

- Gives glass a grey hue with sandblasted effect
- Modernize space with a dramatic look
- Softly diffuses light while providing privacy
- Can be custom cut for a decorative or patterned appearance
- Helps shield harmful ultraviolet rays

Specifications

Product Name	Graphite
Product Series	Color Frost Series
Film Type	Vinyl
Adhesive Type	Pressure-sensitive
Usage	Interior
Width	60"
Film Thickness (excludes liner)	.006"

Installation and Limited Warranty

LLumar iLLusions are professionally installed by a global network of LLumar dealers in accordance with factory procedures.

While installation is fast, with minimal disruption to tenants or contractors, the films are highly durable and backed by a manufacturer's limited warranty. Your dealer can provide you with technical information and warranty details.

Contact Information

Call 1-800-851-7781 or visit solutions.llumar.com/commercial to learn more.

Performance Data

	% Visible Light Transmittance	% Diffuse Visible Light Reflectance (exterior)	Privacy Film Rating
Clear Glass 1/8" (3mm) single pane	90	8	0
Graphite 1/8" (3mm) single pane	35	6	6

Privacy Film Rating

This number, between 0 (clear) and 10 (opaque), represents the relative difficulty an observer has in identifying the nature and character of an object located on the opposite side of the glass pane, with the observer and the object both located at least 2 feet from the filmed pane. The number is intended to be a guide only.

*This reflectance value is a standard specular reflectance value
For the most current data please go to LLumar.com/nar-deco-specs



LLumar.com

