

LLumar® iLLusions™ Decorative Window Film
Nature Series
Subtle Waves



SPECIFICATION SHEET



To view this product and the rest of the LLumar® iLLusions™ line, please visit LLumar.com/decofilmviewer

Specifications

Product Name	Subtle Waves
Product Series	Nature Series
Film Type	Vinyl
Adhesive Type	Pressure-sensitive
Usage	Interior
Width	60", 48"
Film Thickness (excludes liner)	.005"

Performance Data

	% Visible Light Transmittance	% Diffuse Visible Light Reflectance (exterior)	Privacy Film Rating
Clear Glass 1/8" (3mm) single pane	90	8	0
Subtle Waves 1/8" (3mm) single pane	88	12	4

For the most current data please go to LLumar.com/nar-deco-specs

Product Description

Link natural outside elements to interior landscapes with our embossed Nature Series decorative films inspired by water, foliage and sand. Explore and bring in the essence of the outdoors to convert uninteresting spaces into peaceful places.

Nature-themed films let you create privacy, maintain natural light, and bring tranquility and uplifting energy to interiors.

Benefits and selection criteria

- Light wavy pattern adds dimension to glass
- Obscures object definition for elevated privacy
- Refracts light and simulates texture without designer glass cost
- Helps shield harmful ultraviolet rays

Installation and Limited Warranty

LLumar iLLusions are professionally installed by a global network of LLumar dealers in accordance with factory procedures.

While installation is fast, with minimal disruption to tenants or contractors, the films are highly durable and backed by a manufacturer's limited warranty. Your dealer can provide you with technical information and warranty details.

Contact Information

Call 1-800-851-7781 or visit solutions.llumar.com/commercial to learn more.

Privacy Film Rating

This number, between 0 (clear) and 10 (opaque), represents the relative difficulty an observer has in identifying the nature and character of an object located on the opposite side of the glass pane, with the observer and the object both located at least 2 feet from the filmed pane. The number is intended to be a guide only.